





RIV FIRE TRUCKS

RAPID INTERVENTION VEHICLE



SPECIFICATIONS

Firetiger

PURPOSE

- For response of first emergency.
- To catch up in the small industry and basic fire.
- Reduce the work force (two person operated).

PROPOSED CHASSIS DETAIL

- HINO DUTRO JNR
- ISUZU NKR
- MASTER FOTON (Chinese option)
- JAC (Chinese option)
- Any other

WATER TANK

Capacity: 1000 to 1500 litres.

Material: Fibre Glass.

Other option: Galvanised iron, stainless steel and mild steel,

FIRE PUMP

Option 1:

Centrifugal, 2 1/2" suction x 1.5" delivery,

driven by 13 HP Honda petrol engine.

Maximum output: 100 GPM (450 liters per minute).

Maximum pressure: 70 PSI (5 bar).

Start: Electric (battery) and pull rope mounted in base frame

and fixed on the chassis frame.

Option 2:

TOHATSU, 2-Stroke, 2-cylinder, water cooled gasoline engine.

Total piston displacement: 617cc.

Max. output: 40.2 HP/30 KW.

Starter motor and automatic recoil system.

Pump: Single suction, single stage, high pressure turbine

pump.

Priming by rotary vane pump.

FOAM EQUIPMENT

- Foam proportioner, around the pump, with 0-6% selection or balanced automatic proportioner.
- Water /Foam single barrel monitor.

HOSE REEL

Fitted with 3/4" x 100 ft. of high pressure hose with jet spray nozzle.

WARNING EQUIPMENT

Bar lights with PA (Public Address) system and flashing lights.

Head Office

Faisalabad

Tel: (041) 787 001 Fax: (041) 787 002 E-mail: fsd@firechief.com.pk

Tel: (021) 3453 8945 Fax: (021) 3453 8946

Islamabad

Tel: (051) 486 1014 Fax: (051) 486 1015 E-mail: north@firechief.com.pk

BODY WORK

Elegantly designed and smartly finished, using quality mild steel angles, channels and sheets of suitable sizes. to enable it to withstand maximum wear and tear on dusty and bumpy roads. Outer covering of 18 gauge sheet.

Fixed ladders are provided at the rear for climbing to the vehicle top.

Protective railings are provided along the lengths of the vehicle top.

All floors and walking platform covered with antislip chequer plates/strips.

LOCKERS

Suitably provided on the appliance to allow maximum space for carrying hoses and other sundries. To protect the stores, lockers are provided with aluminum roller shutters. Lights fitted inside lockers.

PAINTING AND FINISHING

Body, including cabs is finished in fire engine red. Interior and lockers painted in grey or matching colours.

SUCTION HOSE TUNNELS

Two straight tubular tunnels are provided at the top, each to accommodate on length of suction hose 4"x 10 ft. with couplings.

FIRE FIGHTING ACCESSORIES

On request, as per customer's specification or according to individual requirements.

RESCUE TOOLS

Combi Tool, Spreader, Cutter upon request can be accomodated.



123/3, Quaid-e-Azam Industrial Estate, Haseen Habib Road, Kot Lakhpat, Lahore. Tel: 042 3512 3195-96, Fax: 042 3512 3197 E-mail: info@firechief.com.pk

Karachi

E-mail: khi@firechief.com.pk

/haseenhabibcorp